

P-302

Proximity Hotel Lock



RETH INTERNATIONAL GROUP

UEI HAUR ENTERPRISE CO., LTD.
NO.282 TZYH CHYANG RD, CHANG HUA, TAIWAN. R.O.C.

TEL:886-4-7231908
FAX:886-4-7231780



E-mail:reth.tw@msa.hinet.net
<http://www.rethlock.com.tw>

Feature Introduce

1. The cover is made of die cast zinc alloy construction, matches the copper handle 2. knob with hard endurance and waterproof.
2. The hard and beautiful shaped pry and saw meet the American UL national security standard.
3. The electro coating process provides variety color finishes upon request.
4. The device can used for present door replacement or newly installation.
5. Power saving logic design uses only four standard 1.5V (AA) alkaline batteries providing sufficient power for 8 to 12 months of use.
6. When door opened from outside, power will automatically switch to energy saving mode after 6 seconds; meanwhile, when opened from inside, no power required.
7. The lock equipped with low battery alarm beep and led.
8. When the inside lock is on, the master card allows to open the door, when in other condition, a special tool opens up the lock cover which allow the spare key to be used for door opening.
9. A metal protrusion in the center of the lock body cover indicates that the door is double-locked.
10. Guest card and user card can be authorized, and the same card number can do infinite to extend.
11. The guest card can overlay the former card for upgrade.
12. If the user card got lost, the door lock allows oneself to cancel convenience and security.
13. The cards can be classified into master card, initial card, guest card, guest lock-out card, and user card.
14. Each lock is entirely self-contained. No extra wiring required for convenience and simplicity.

Function Description

- The security managers can program the master card, then authorize the guest card and user card for operation.
- No on-line computer is need for master card operation programming.
- The key card's high compatibility avoids carry multiple cards.
- The master card allows programming the lock in, either normal condition or temporary condition.
- The inside lock detects both the master and guest card for unlock.
- The guest card can detect itself as of newly issued or former card replacement.
- Guest lock-out card can prohibit the guest card until the master card to release.

Open Method

- After card is sensed, beep one sound, then green light ignite.
- After pressing handle knob, it can be opened within 6 seconds.
- After 6 seconds of door opening, the lock will turn into automatic self lock mode.

Specification

| | |
|---------------------|---|
| Power | DC6V, four standard 1.5V (AA) |
| Capacity | user card (circulating overlay) and common card |
| Time | 6 seconds |
| Card specification | 125KHZ 182bits, Temic |
| Low battery Warning | DC5V |

• We reserve the right to alter designs and specifications without prior notice.

